



- SC Adapter(shot flange with innner shutter



- Application










Add: No. A401, 1th Bldg, Yingzhan Electronic Park,Longtian Community, Longtian Street, Pingshan District 518118,
Shenzhen City, Guangdong Province, China.
Tel:+86-755-26857429 27510098 Fax：86-755-27510738 E-mail：sales@zgttech.com http：//www.zgttech.com

ZGT Optical Comm Limited

- Dimention




| Key Specifications | |
|---|---|
| Insertion Loss | ⩽0.2dB |
| Operatin Temperature | -40℃ to+85℃ |
| Storage Temperature | -40℃ to+85℃ |
| Size | IEC61754-4 |
| Durability,500 cycles | IEC61300-2-2 |
| Strength of coupling mechanism, 40N, 5N/s, 120s | IEC61300-2-6 |
| Damp Heat test, +25°C to +55°C, >90% RH, 6 cycles | IEC61300-2-46 |
| thermal change test , +75°C to -40°C, 1h at extreme temperature, 1°C/min, 12 cycles | IEC61300-2-22 |
| Dust test | GR326_4.4.4.1 |

Add: No. A401, 1th Bldg, Yingzhan Electronic Park,Longtian Community, Longtian Street, Pingshan District 518118,
Shenzhen City, Guangdong Province, China.
Tel:+86-755-26857429 27510098 Fax：86-755-27510738 E-mail：sales@zgttech.com http：//www.zgttech.com