

LC Adaptor with Unique Internal Shutter

This LC adapters are with unique shutter inside, they are dust and laser free, the assembly size is IEC compliant. LC Duplex and Quad are available.
Standard: GR326, IEC.
RoHS and REACH Compliant
Fire Resistance: UL 94V-0
Color: Blue, Green, Beige, or customer required.


Code: ZZTAD-LC21




Assembly Size:



Code: ZZTAD-LC22



Assembly Size:



地址：中国深圳市宝安区福永街道桥头社区正中工业园八栋四楼
Add：4F, 8building, Zheng Zhong Industrial Zone, Qiao Tou Community of Fu Yong Town, Bao an District, Shenzhen, China
邮编(P.C.)：518100
电话(Tel)：+86-755-26857429 27510098
邮件(E-mail)：sales@zgttech.com
传真(Fax)：86-755-27510738
网址(http)：//www.zgttech.com

Unique Internal Shutter in SC SX Adapter

Key Specifications

Insertion Loss	≤0.2dB
Durability	500 mates
Operating Temperature	-40°C to +85 °C
Storage Temperature	-40°C to +85 °C

Environmental and Mechanism

Inspection	Test condition	Test method	IL Value
Vibration	10-55Hz, 30min	IEC61300-2-1	Δ ≤0.2dB
Mating Durability	500 Mating, clean every 25 mating.	IEC61300-2-2	Δ ≤0.2dB
Impact	1.5mH, 2.25mL, 5 drops	IEC61300-2-12	Δ ≤0.2dB
Strength of Coupling Mechanism	50N, 10Min		Δ ≤0.2dB
Salt Spray	35℃, 5%, 48H	IEC60068-2-11	Δ ≤0.2dB
Temperature Cycling	-40℃ to +75℃, 40 cycles	IEC61300-2-22	Δ ≤0.2dB

地址：中国深圳市宝安区福永街道桥头社区正中工业园八栋四楼
Add：4F, 8building, Zheng Zhong Industrial Zone, Qiao Tou Community of Fu Yong Town, Bao an District, Shenzhen, China
邮编(P.C.)：518100
电话(Tel)：+86-755-26857429 27510098
邮件(E-mail)：sales@zgttech.com
传真(Fax)：86-755-27510738
网址(http)：//www.zgttech.com